



## ASYMMETRICAL TYPE

### SPECIFICATION

#### HOUSING

- DIE-FORMED COLD-ROLLED STEEL  
AVAILABLE IN  0.4,  0.6,  0.8 mm.  
STEEL THICKNESS
- ALL METAL PART ARE RUST-PROOFED AFTER  
FABRICATION TO PREVENT ANY CORROSION  
(ZINE PHOSPHATE)
- FINISHED WITH HIGH GRADE EPOXY POLYESTER  
POWDER COATING
- G5 ROTARY LOCKED LAMP HOLDER
- THW  0.5 sqmm./105c  1.0 sqmm./70c  
WIRING CABLE

#### REFLECTOR (WAS)

- WHITE STOVE ENAMEL STEEL SHEEL

#### OPTION REFLECTOR (WAA)

- 99.80% PURITY ANODIZED ALUMINIUM  
REFLECTOR TO PROVIDE TOTAL REFLECTANCE OF  
 TR 87%  TR 95% FOR MIRROR FINISH

#### INSTALLATION

- WALL MOUNT

### DIMENSIONS (mm.)

MODEL	TYPE	W	L	H
WAS1/1S	T5	36	570	80
WAS1/1L	T5	36	1170	80
WAA1/1S	T5	36	570	80
WAA1/1L	T5	36	1170	80

