



ASYMMETRICAL TYPE

SPECIFICATION

HOUSING

- DIE-FORMED COLD-ROLLED STEEL
AVAILABLE IN ☐ 0.4 , ☐ 0.6 , ☐ 0.8 mm.
STEEL THICKNESS
- ALL METAL PART ARE RUST-PROOFED AFTER
FABRICATION TO PREVENT ANY CORROSION
(ZINE PHOSPHATE)
- FINISHED WITH HIGH GRADE EPOXY POLYESTER
POWDER COATING
- G13 ROTARY LOCKED OR SPRING LOAD
LAMP HOLDER
- THW ☐ 0.5 sqmm./105c ☐ 1.0 sqmm./70c
WIRING CABLE

REFLECTOR (WAS)

- WHITE STOVE ENAMEL STEEL SHEEL

OPTION REFLECTOR (WAA)

- 99.80% PURITY ANODIZED ALUMINIUM
REFLECTOR TO PROVIDE TOTAL REFLECTANCE OF
☐ TR 87% ☐ TR 95% FOR MIRROR FINISH

INSTALLATION

- WALL MOUNT

DIMENSIONS (mm.)

MODEL	TYPE	W	L	H
WAS1/1S	T8	60	612	125
WAS1/1S/S	T8	60	635	125
WAS1/1L	T8	60	1222	125
WAS1/1L/S	T8	60	1245	125
WAA1/1S	T8	60	612	125
WAA1/1S/S	T8	60	635	125
WAA1/1L	T8	60	1222	125
WAA1/1L/S	T8	60	1245	125

