



## CLEAN ROOM TYPE

### SPECIFICATION

#### HOUSING

- DIE-FORMED COLD-ROLLED STEEL  
AVAILABLE IN  0.4,  0.6,  0.8 mm.  
STEEL THICKNESS
- ALL METAL PART ARE RUST-PROOFED AFTER  
FABRICATION TO PREVENT ANY CORROSION  
(ZINE PHOSPHATE)
- FINISHED WITH HIGH GRADE EPOXY POLYESTER  
POWDER COATING
- G13 ROTARY LOCKED LAMP HOLDER
- THW  0.5 sqmm./105c  1.0 sqmm./70c  
WIRING CABLE

#### REFLECTOR

- 99.80% PURITY ANODIZED ALUMINIUM  
REFLECTOR TO PROVIDE TOTAL REFLECTANCE OF  
 TR 87%  TR 95% FOR MIRROR FINISH

#### DIFFUSER

- FOR PRISMATIC ACRYLIC DIFFUSER (PM)
- FOR OPAL ACRYLIC DIFFUSER (OP)
- FOR STIPLE ACRYLIC DIFFUSER (ST)
- FOR CLEAR ACRYLIC DIFFUSER (CL)

#### INSTALLATION

- AVAILABLE IN RECESSED T-BAR OR CONCEAL CEILING
- SERVICE DOOR TYPE (FRONT OPENING)

### DIMENSIONS (mm.)

MODEL	TYPE	W	W1	L	L1	H	CEILING CUT OUT (mm.) A x B
WCR3/1S/F-EX	T8	300	271	612	640	90	275 x 617
WCR3/2S/F-EX	T8	300	271	612	640	90	275 x 617
WCR3/1L/F-EX	T8	300	271	1220	1250	90	275 x 1225
WCR3/2L/F-EX	T8	300	271	1220	1250	90	275 x 1225
WCR6/2S/F-EX	T8	600	571	612	640	90	575 x 617
WCR6/3S/F-EX	T8	600	571	612	640	90	575 x 617
WCR6/4S/F-EX	T8	600	571	612	640	90	575 x 617
WCR6/2L/F-EX	T8	600	571	1220	1250	90	575 x 1225
WCR6/3L/F-EX	T8	600	571	1220	1250	90	575 x 1225
WCR6/4L/F-EX	T8	600	571	1220	1250	90	575 x 1225

