



CLEAN ROOM TYPE

SPECIFICATION

HOUSING

- DIE-FORMED COLD-ROLLED STEEL AVAILABLE IN 0.4 , 0.6 , 0.8 mm. STEEL THICKNESS
- ALL METAL PART ARE RUST-PROOFED AFTER FABRICATION TO PREVENT ANY CORROSION (ZINE PHOSPHATE)
- FINISHED WITH HIGH GRADE EPOXY POLYESTER POWDER COATING
- G13 ROTARY LOCKED LAMP HOLDER
- THW 0.5 sqmm./105c 1.0 sqmm./70c WIRING CABLE

REFLECTOR

- 99.80% PURITY ANODIZED ALUMINIUM REFLECTOR TO PROVIDE TOTAL REFLECTANCE OF TR 87% TR 95% FOR MIRROR FINISH

DIFFUSER

- FOR PRISMATIC ACRYLIC DIFFUSER (PM)
- FOR OPAL ACRYLIC DIFFUSER (OP)
- FOR STIPLE ACRYLIC DIFFUSER (ST)
- FOR CLEAR ACRYLIC DIFFUSER (CL)

INSTALLATION

- AVAILABLE IN RECESSED T-BAR OR CONCEAL CEILING
- SERVICE DOOR TYPE (FRONT OPENING)

DIMENSIONS (mm.)

MODEL	TYPE	W	W1	L	L1	H	CEILING CUT OUT (mm.) A x B
WCR3/1S/F	T8	295	257	612	636	90	270 x 617
WCR3/2S/F	T8	295	257	612	636	90	270 x 617
WCR3/1L/F	T8	295	257	1220	1245	90	270 x 1225
WCR3/2L/F	T8	295	257	1220	1245	90	270 x 1225

