



CLEAN ROOM TYPE

SPECIFICATION

HOUSING

- DIE-FORMED COLD-ROLLED STEEL
AVAILABLE IN 0.4, 0.6, 0.8 mm.
STEEL THICKNESS
- ALL METAL PART ARE RUST-PROOFED AFTER
FABRICATION TO PREVENT ANY CORROSION
(ZINE PHOSPHATE)
- FINISHED WITH HIGH GRADE EPOXY POLYESTER
POWDER COATING
- G13 ROTARY LOCKED LAMP HOLDER
- THW 0.5 sqmm./105c 1.0 sqmm./70c
WIRING CABLE

REFLECTOR

- 99.80% PURITY ANODIZED ALUMINIUM
REFLECTOR TO PROVIDE TOTAL REFLECTANCE OF
 TR 87% TR 95% FOR MIRROR FINISH

DIFFUSER

- FOR PRISMATIC ACRYLIC DIFFUSER (PM)
- FOR OPAL ACRYLIC DIFFUSER (OP)
- FOR STIPLE ACRYLIC DIFFUSER (ST)
- FOR CLEAR ACRYLIC DIFFUSER (CL)

INSTALLATION

- AVAILABLE IN RECESSED T-BAR OR CONCEAL CEILING
- SERVICE DOOR TYPE (BACK OPENING)

DIMENSIONS (mm.)

MODEL	TYPE	W	W1	L	L1	H	CEILING CUT OUT (mm.) A x B
WCR3/2S/B	T8	300	275	612	640	110	280 x 617
WCR6/2S/B	T8	600	575	612	640	110	580 x 617
WCR6/3S/B	T8	600	575	612	640	110	580 x 617
WCR3/2L/B	T8	300	275	1220	1245	110	280 x 1225
WCR6/2L/B	T8	600	575	1220	1245	110	580 x 1225
WCR6/3L/B	T8	600	575	1220	1245	110	580 x 1225

