

# FLUORESCENT



## DIFFUSER TYPE

### SPECIFICATION

#### HOUSING

- DIE-FORMED COLD-ROLLED STEEL  
AVAILABLE IN  0.4,  0.6,  0.8 mm.  
STEEL THICKNESS
- ALL METAL PART ARE RUST-PROOFED AFTER  
FABRICATION TO PREVENT ANY CORROSION  
(ZINE PHOSPHATE)
- FINISHED WITH HIGH GRADE EPOXY POLYESTER  
POWDER COATING
- G5 ROTARY LOCKED LAMP HOLDER
- THW  0.5 sqmm./105c  1.0 sqmm./70c  
WIRING CABLE

#### REFLECTOR

- 99.80% PURITY ANODIZED ALUMINIUM  
REFLECTOR TO PROVIDE TOTAL REFLECTANCE OF  
 TR 87%  TR 95% FOR MIRROR FINISH

#### DIFFUSER

- FOR PRISMATIC ACRYLIC DIFFUSER (PM)
- FOR OPAL ACRYLIC DIFFUSER (OP)
- FOR STIPLE ACRYLIC DIFFUSER (ST)
- FOR CLEAR ACRYLIC DIFFUSER (CL)

#### INSTALLATION

- AVAILABLE IN RECESSED T-BAR OR CONCEAL CEILING

### DIMENSIONS (mm.)

MODEL	TYPE	W	W1	L	L1	H	CEILING CUT OUT (mm.) A x B
WDR1/1/1S	T5	145	107	570	595	110	120 x 575
WDR1/3/1S	T5	295	257	570	595	80	270 x 575
WDR1/3/2S	T5	295	257	570	595	80	270 x 575
WDR1/1/1L	T5	145	107	1173	1197	110	120 x 1178
WDR1/3/1L	T5	295	257	1173	1197	80	270 x 1178
WDR1/3/2L	T5	295	257	1173	1197	80	270 x 1178

