



DIFFUSER TYPE

SPECIFICATION

HOUSING

- DIE-FORMED COLD-ROLLED STEEL
AVAILABLE IN ☐ 0.4, ☐ 0.6, ☐ 0.8 mm.
STEEL THICKNESS
- ALL METAL PART ARE RUST-PROOFED AFTER
FABRICATION TO PREVENT ANY CORROSION
(ZINE PHOSPHATE)
- FINISHED WITH HIGH GRADE EPOXY POLYESTER
POWDER COATING
- G13 ROTARY LOCKED LAMP HOLDER
- THW ☐ 0.5 sqmm./105c ☐ 1.0 sqmm./70c
WIRING CABLE

REFLECTOR

- 99.80% PURITY ANODIZED ALUMINIUM
REFLECTOR TO PROVIDE TOTAL REFLECTANCE OF
☐ TR 87% ☐ TR 95% FOR MIRROR FINISH

DIFFUSER

- ☐ FOR PRISMATIC ACRYLIC DIFFUSER (PM)
- ☐ FOR OPAL ACRYLIC DIFFUSER (OP)
- ☐ FOR STIPLE ACRYLIC DIFFUSER (ST)
- ☐ FOR CLEAR ACRYLIC DIFFUSER (CL)
- EXTRUDE ALUMINIUM FRAME

INSTALLATION

- AVAILABLE IN RECESSED T-BAR OR CONCEAL CEILING

DIMENSIONS (mm.)

MODEL	TYPE	W	W1	L	L1	H	CEILING CUT OUT (mm.) A x B
WDR2/3/1S	T8	300	275	612	600	95	280 x 580
WDR2/3/2S	T8	300	275	612	600	95	280 x 580
WDR2/3/1L	T8	300	275	1220	1200	95	280 x 1180
WDR2/3/2L	T8	300	275	1220	1200	95	280 x 1180

