



DIFFUSER TYPE

SPECIFICATION

HOUSING

- DIE-FORMED COLD-ROLLED STEEL
AVAILABLE IN 0.4 , 0.6 , 0.8 mm.
STEEL THICKNESS
- ALL METAL PART ARE RUST-PROOFED AFTER
FABRICATION TO PREVENT ANY CORROSION
(ZINE PHOSPHATE)
- FINISHED WITH HIGH GRADE EPOXY POLYESTER
POWDER COATING
- G5 ROTARY LOCKED LAMP HOLDER
- THW 0.5 sqmm./105c 1.0 sqmm./70c
WIRING CABLE

REFLECTOR

- 99.80% PURITY ANODIZED ALUMINIUM
REFLECTOR TO PROVIDE TOTAL REFLECTANCE OF
 TR 87% TR 95% FOR MIRROR FINISH

DIFFUSER

- FOR PRISMATIC ACRYLIC DIFFUSER (PM)
- FOR OPAL ACRYLIC DIFFUSER (OP)
- FOR STIPLE ACRYLIC DIFFUSER (ST)
- FOR CLEAR ACRYLIC DIFFUSER (CL)
- EXTRUDE ALUMINIUM FRAME

INSTALLATION

- AVAILABLE IN RECESSED T-BAR OR CONCEAL CEILING

DIMENSIONS (mm.)

MODEL	TYPE	W	W1	L	L1	H	CEILING CUT OUT (mm.) A x B
WDR2/6/2S	T5	600	575	575	600	95	580 x 580
WDR2/6/3S	T5	600	575	575	600	95	580 x 580
WDR2/6/4S	T5	600	575	575	600	95	580 x 580
WDR2/6/2L	T5	600	575	1174	1200	95	580 x 1180
WDR2/6/3L	T5	600	575	1174	1200	95	580 x 1180
WDR2/6/4L	T5	600	575	1174	1200	95	580 x 1180

