



## DIFFUSER TYPE

### SPECIFICATION

#### HOUSING

- DIE-FORMED COLD-ROLLED STEEL  
AVAILABLE IN  0.4 ,  0.6 ,  0.8 mm.  
STEEL THICKNESS
- ALL METAL PART ARE RUST-PROOFED AFTER  
FABRICATION TO PREVENT ANY CORROSION  
(ZINE PHOSPHATE)
- FINISHED WITH HIGH GRADE EPOXY POLYESTER  
POWDER COATING
- G13 ROTARY LOCKED LAMP HOLDER
- THW  0.5 sqmm./105c  1.0 sqmm./70c  
WIRING CABLE

#### REFLECTOR

- 99.80% PURITY ANODIZED ALUMINIUM  
REFLECTOR TO PROVIDE TOTAL REFLECTANCE OF  
 TR 87%  TR 95% FOR MIRROR FINISH

#### DIFFUSER

- FOR PRISMATIC ACRYLIC DIFFUSER (PM)
- FOR OPAL ACRYLIC DIFFUSER (OP)
- FOR STIPLE ACRYLIC DIFFUSER (ST)
- FOR CLEAR ACRYLIC DIFFUSER (CL)
- EXTRUDE ALUMINIUM FRAME

#### INSTALLATION

- AVAILABLE IN RECESSED T-BAR OR CONCEAL CEILING

#### DIMENSIONS (mm.)

MODEL	TYPE	W	W1	L	L1	H	CEILING CUT OUT (mm.) A x B
WDR2/6/2S	T8	600	575	612	600	95	580 x 580
WDR2/6/3S	T8	600	575	612	600	95	580 x 580
WDR2/6/4S	T8	600	575	612	600	95	580 x 580
WDR2/6/2L	T8	600	575	1220	1200	95	580 x 1180
WDR2/6/3L	T8	600	575	1220	1200	95	580 x 1180
WDR2/6/4L	T8	600	575	1220	1200	95	580 x 1180

