



DIFFUSER TYPE

SPECIFICATION

HOUSING

- DIE-FORMED COLD-ROLLED STEEL
AVAILABLE IN ☐ 0.4 , ☐ 0.6 , ☐ 0.8 mm.
STEEL THICKNESS
- ALL METAL PART ARE RUST-PROOFED AFTER
FABRICATION TO PREVENT ANY CORROSION
(ZINE PHOSPHATE)
- FINISHED WITH HIGH GRADE EPOXY POLYESTER
POWDER COATING
- (G5, G13) ROTARY LOCKED LAMP HOLDER
- THW ☐ 0.5 sqmm./105c ☐ 1.0 sqmm./70c
WIRING CABLE

REFLECTOR

- 99.80% PURITY ANODIZED ALUMINIUM
REFLECTOR TO PROVIDE TOTAL REFLECTANCE OF
☐ TR 87% ☐ TR 95% FOR MIRROR FINISH

DIFFUSER

- ☐ FOR PRISMATIC ACRYLIC DIFFUSER (PM)
- ☐ FOR OPAL ACRYLIC DIFFUSER (OP)
- ☐ FOR STIPLE ACRYLIC DIFFUSER (ST)
- ☐ FOR CLEAR ACRYLIC DIFFUSER (CL)

INSTALLATION

- SURFACE OR SUSPENDED MOUNTING

DIMENSIONS (mm.)

MODEL	TYPE	W	L	H
WDS1/1/1S	T5 ,T8	151	635	80
WDS1/3/1S	T5 ,T8	301	616	80
WDS1/3/2S	T5 ,T8	301	616	80
WDS1/1/1L	T5 ,T8	151	1245	80
WDS1/3/1L	T5 ,T8	301	1226	80
WDS1/3/2L	T5 ,T8	301	1226	80

