



DIFFUSER TYPE

SPECIFICATION

HOUSING

- DIE-FORMED COLD-ROLLED STEEL
AVAILABLE IN ☐ 0.4, ☐ 0.6, ☐ 0.8 mm.
STEEL THICKNESS
- ALL METAL PART ARE RUST-PROOFED AFTER
FABRICATION TO PREVENT ANY CORROSION
(ZINE PHOSPHATE)
- FINISHED WITH HIGH GRADE EPOXY POLYESTER
POWDER COATING
- G13 ROTARY LOCKED LAMP HOLDER
- THW ☐ 0.5 sqmm./105c ☐ 1.0 sqmm./70c
WIRING CABLE

DIFFUSER

- ☐ FOR PRISMATIC ACRYLIC DIFFUSER (PM)
- ☐ FOR OPAL ACRYLIC DIFFUSER (OP)
- ☐ FOR STIPLE ACRYLIC DIFFUSER (ST)
- ☐ FOR CLEAR ACRYLIC DIFFUSER (CL)

INSTALLATION

- WALL MOUNT

DIMENSIONS (mm.)

| MODEL | TYPE | W | L | H |
|----------|------|----|------|----|
| WDS10/1S | T8 | 75 | 626 | 90 |
| WDS10/1L | T8 | 75 | 1230 | 90 |

