



FLUORESCENT HIGH BAY TYPE

SPECIFICATION

HOUSING

- DIE-FORMED COLD-ROLLED STEEL AVAILABLE IN 0.8 mm. STEEL THICKNESS
- ALL METAL PART ARE RUST-PROOFED AFTER FABRICATION TO PREVENT ANY CORROSION (ZINE PHOSPHATE)
- FINISHED WITH HIGH GRADE EPOXY POLYESTER POWDER COATING
- (G5, G13) ROTARY LOCKED LAMP HOLDER
- THW ☐ 0.5 sqmm./105c ☐ 1.0 sqmm./70c WIRING CABLE

REFLECTOR

- 99.80% PURITY ANODIZED ALUMINIUM REFLECTOR TO PROVIDE TOTAL REFLECTANCE OF ☐ TR 87% ☐ TR 95% FOR MIRROR FINISH

DIFFUSER

- FOR CLEAR ACRYLIC DIFFUSER
- RUBBER AROUND FRONT COVER TO PROTECT DUST
- STEEL CLIP LOCK AT FRONT COVER

INSTALLATION

- SURFACE AND PENDENT MOUNTING

DIMENSIONS (mm.)

MODEL	TYPE	W	L	H
WFB2/2L	T5	330	1210	95
WFB2/3L	T5	480	1210	95
WFB2/4L	T5	480	1210	95
WFB2/2L	T8	330	1230	95
WFB2/3L	T8	480	1230	95
WFB2/4L	T8	480	1230	95

