



## INDUSTIRAL TYPE

### SPECIFICATION

#### HOUSING

- DIE-FORMED COLD-ROLLED STEEL  
AVAILABLE IN  0.4,  0.6,  0.8 mm.  
STEEL THICKNESS
- ALL METAL PART ARE RUST-PROOFED AFTER  
FABRICATION TO PREVENT ANY CORROSION  
(ZINE PHOSPHATE)
- FINISHED WITH HIGH GRADE EPOXY POLYESTER  
POWDER COATING
- G13 ROTARY LOCKED OR SPRING LOAD  
LAMP HOLDER
- THW  0.5 sqmm./105c  1.0 sqmm./70c  
WIRING CABLE

#### REFLECTOR

- 99.80% PURITY ANODIZED ALUMINIUM  
REFLECTOR TO PROVIDE TOTAL REFLECTANCE OF  
 TR 87%  TR 95% FOR MIRROR FINISH
- PARABOLIC REFLECTOR MACHINED TO PROVIDE  
OPTIMUM OPTICAL PERFORMANCE FOR LONGITUDINAL

#### OPTION REFLECTOR

- WHITE STOVE ENAMEL STEEL SHEEL (WIS)

#### INSTALLATION

- SURFACE OR SUSPENDED MOUNTING

#### DIMENSIONS (mm.)

MODEL	TYPE	W	L	H
WIA4/2S	T8	200	612	80
WIA4/2S/S	T8	200	635	80
WIA4/2L	T8	200	1220	80
WIA4/2L/S	T8	200	1245	80
WIS4/2S	T8	200	612	80
WIS4/2S/S	T8	200	635	80
WIS4/2L	T8	200	1220	80
WIS4/2L/S	T8	200	1245	80

