



INDUSTIRAL TYPE

SPECIFICATION

HOUSING

- DIE-FORMED COLD-ROLLED STEEL AVAILABLE IN 0.4 , 0.6 , 0.8 mm. STEEL THICKNESS
- ALL METAL PART ARE RUST-PROOFED AFTER FABRICATION TO PREVENT ANY CORROSION (ZINE PHOSPHATE)
- FINISHED WITH HIGH GRADE EPOXY POLYESTER POWDER COATING
- G13 ROTARY LOCKED OR SPRING LOAD LAMP HOLDER
- THW 0.5 sqmm./105c 1.0 sqmm./70c WIRING CABLE

REFLECTOR

- 99.80% PURITY ANODIZED ALUMINIUM REFLECTOR TO PROVIDE TOTAL REFLECTANCE OF TR 87% TR 95% FOR MIRROR FINISH
- PARABOLIC REFLECTOR MACHINED TO PROVIDE OPTIMUM OPTICAL PERFORMANCE FOR LONGITUDINAL

OPTION REFLECTOR

- WHITE STOVE ENAMEL STEEL SHEEL (WIS)

INSTALLATION

- SURFACE OR SUSPENDED MOUNTING

DIMENSIONS (mm.)

MODEL	TYPE	W	L	H
WIA6/1S	T8	150	612	80
WIA6/1S/S	T8	150	635	80
WIA6/1L	T8	150	1220	80
WIA6/1L/S	T8	150	1245	80
WIS6/1S	T8	150	612	80
WIS6/1S/S	T8	150	635	80
WIS6/1L	T8	150	1220	80
WIS6/1L/S	T8	150	1245	80

