



INDUSTIRAL TYPE

SPECIFICATION

HOUSING

- DIE-FORMED COLD-ROLLED STEEL
AVAILABLE IN 0.4, 0.6, 0.8 mm.
STEEL THICKNESS
- ALL METAL PART ARE RUST-PROOFED AFTER
FABRICATION TO PREVENT ANY CORROSION
(ZINE PHOSPHATE)
- FINISHED WITH HIGH GRADE EPOXY POLYESTER
POWDER COATING
- G13 SPRING LOAD LAMP HOLDER
- THW 0.5 sqmm./105c 1.0 sqmm./70c
WIRING CABLE

REFLECTOR

- 99.80% PURITY ANODIZED ALUMINIUM
REFLECTOR TO PROVIDE TOTAL REFLECTANCE OF
 TR 87% TR 95% FOR MIRROR FINISH
- PARABOLIC REFLECTOR MACHINED TO PROVIDE
OPTIMUM OPTICAL PERFORMANCE FOR LONGITUDINAL

OPTION REFLECTOR

- WHITE STOVE ENAMEL STEEL SHEEL (WIS)

INSTALLATION

- SURFACE OR SUSPENDED MOUNTING

DIMENSIONS (mm.)

MODEL	TYPE	W	L	H
WIA7/1S/S	T8	150	635	100
WIA7/1L/S	T8	150	1245	100
WIS7/1S/S	T8	150	635	100
WIS7/1L/S	T8	150	1245	100

