



PROFILE LOUVER TYPE

SPECIFICATION

HOUSING

- DIE-FORMED COLD-ROLLED STEEL
AVAILABLE IN □ 0.4, □ 0.6, □ 0.8 mm.
STEEL THICKNESS
- ALL METAL PART ARE RUST-PROOFED AFTER
FABRICATION TO PREVENT ANY CORROSION
(ZINE PHOSPHATE)
- FINISHED WITH HIGH GRADE EPOXY POLYESTER
POWDER COATING
- G13 ROTARY LOCKED LAMP HOLDER
- THW □ 0.5 sqmm./105c □ 1.0 sqmm./70c
WIRING CABLE

REFLECTOR & LOUVER

- 99.80% PURITY ANODIZED ALUMINIUM
REFLECTOR TO PROVIDE TOTAL REFLECTANCE OF
□ TR 87% □ TR 95% FOR MIRROR FINISH
- PARABOLIC REFLECTOR MACHINED TO PROVIDE
OPTIMUM OPTICAL PERFORMANCE FOR
LONGITUDINAL
- CHRISTMAS TREE PROFILES FOR TRANSVERSAL

INSTALLATION

- AVAILABLE IN RECESSED T-BAR OR CONCEAL CEILING

DIMENSIONS (mm.)

MODEL	TYPE	W	W1	L	L1	H	CEILING CUT OUT (mm.) A x B
WLR1/1/1S	T8	145	107	612	590	110	120 x 572
WLR1/3/1S	T8	295	271	612	590	80	278 x 572
WLR1/3/2S	T8	295	257	612	590	80	270 x 572
WLR1/1/1L	T8	145	107	1220	1197	110	120 x 1178
WLR1/3/1L	T8	295	271	1220	1197	80	278 x 1178
WLR1/3/2L	T8	295	257	1220	1197	80	270 x 1178

