



PROFILE LOUVER TYPE

SPECIFICATION

HOUSING

- DIE-FORMED COLD-ROLLED STEEL
AVAILABLE IN □ 0.4, □ 0.6, □ 0.8 mm.
STEEL THICKNESS
- ALL METAL PART ARE RUST-PROOFED AFTER
FABRICATION TO PREVENT ANY CORROSION
(ZINE PHOSPHATE)
- FINISHED WITH HIGH GRADE EPOXY POLYESTER
POWDER COATING
- G13 ROTARY LOCKED LAMP HOLDER
- THW □ 0.5 sqmm./105c □ 1.0 sqmm./70c
WIRING CABLE

REFLECTOR & LOUVER

- 99.80% PURITY ANODIZED ALUMINIUM
REFLECTOR TO PROVIDE TOTAL REFLECTANCE OF
□ TR 87% □ TR 95% FOR MIRROR FINISH
- PARABOLIC REFLECTOR MACHINED TO PROVIDE
OPTIMUM OPTICAL PERFORMANCE FOR
LONGITUDINAL
- CHRISTMAS TREE PROFILES FOR TRANSVERSAL

INSTALLATION

- AVAILABLE IN RECESSED T-BAR OR CONCEAL CEILING

DIMENSIONS (mm.)

| MODEL | TYPE | W | W1 | L | L1 | H | CEILING CUT OUT (mm.) A x B |
|-----------|------|-----|-----|------|------|----|--------------------------------|
| WLR1/6/2S | T8 | 595 | 557 | 612 | 590 | 80 | 570 x 572 |
| WLR1/6/3S | T8 | 595 | 557 | 612 | 590 | 80 | 570 x 572 |
| WLR1/6/4S | T8 | 595 | 557 | 612 | 590 | 80 | 570 x 572 |
| WLR1/6/2L | T8 | 595 | 557 | 1220 | 1197 | 80 | 570 x 1178 |
| WLR1/6/3L | T8 | 595 | 557 | 1220 | 1197 | 80 | 570 x 1178 |
| WLR1/6/4L | T8 | 595 | 557 | 1220 | 1197 | 80 | 570 x 1178 |

