



PROFILE LOUVER TYPE

SPECIFICATION

HOUSING

- DIE-FORMED COLD-ROLLED STEEL
AVAILABLE IN 0.4, 0.6, 0.8 mm.
STEEL THICKNESS
- ALL METAL PART ARE RUST-PROOFED AFTER FABRICATION TO PREVENT ANY CORROSION (ZINE PHOSPHATE)
- FINISHED WITH HIGH GRADE EPOXY POLYESTER POWDER COATING
- G5 ROTARY LOCKED LAMP HOLDER
- THW 0.5 sqmm./105c 1.0 sqmm./70c
WIRING CABLE

REFLECTOR & LOUVER

- 99.80% PURITY ANODIZED ALUMINIUM REFLECTOR TO PROVIDE TOTAL REFLECTANCE OF TR 87% TR 95% FOR MIRROR FINISH
- PARABOLIC REFLECTOR MACHINED TO PROVIDE OPTIMUM OPTICAL PERFORMANCE FOR LONGITUDINAL
- CHRISTMAS TREE PROFILES FOR TRANSVERSAL
- EXTUDE ALUMINIUM FRAME

INSTALLATION

- AVAILABLE IN RECESSED T-BAR OR CONCEAL CEILING

DIMENSIONS (mm.)

MODEL	TYPE	W	W1	L	L1	H	CEILING CUT OUT (mm.) A x B
WLR2/3/1S	T5	300	275	575	600	85	280 x 580
WLR2/3/2S	T5	300	275	575	600	85	280 x 580
WLR2/3/1L	T5	300	275	1174	1200	85	280 x 1180
WLR2/3/2L	T5	300	275	1174	1200	85	280 x 1180

