



## PROFILE LOUVER TYPE

AIR RETURN

### SPECIFICATION

#### HOUSING

- DIE-FORMED COLD-ROLLED STEEL  
AVAILABLE IN □ 0.4, □ 0.6, □ 0.8 mm.  
STEEL THICKNESS
- ALL METAL PART ARE RUST-PROOFED AFTER  
FABRICATION TO PREVENT ANY CORROSION  
(ZINE PHOSPHATE)
- FINISHED WITH HIGH GRADE EPOXY POLYESTER  
POWDER COATING
- G13 ROTARY LOCKED LAMP HOLDER
- THW □ 0.5 sqmm./105c □ 1.0 sqmm./70c  
WIRING CABLE

#### REFLECTOR & LOUVER

- 99.80% PURITY ANODIZED ALUMINIUM  
REFLECTOR TO PROVIDE TOTAL REFLECTANCE OF  
□ TR 87% □ TR 95% FOR MIRROR FINISH
- PARABOLIC REFLECTOR MACHINED TO PROVIDE  
OPTIMUM OPTICAL PERFORMANCE FOR  
LONGITUDINAL
- CHRISTMAS TREE PROFILES FOR TRANSVERSAL

#### INSTALLATION

- AVAILABLE IN RECESSED T-BAR OR CONCEAL CEILING

#### DIMENSIONS (mm.)

MODEL	TYPE	W	W1	L	L1	H
WLR6/6/2S	T8	595	380	612	590	80
WLR6/6/3S	T8	595	380	612	590	80
WLR6/6/2L	T8	595	380	1220	1197	80
WLR6/6/3L	T8	595	380	1220	1197	80

