

# FLUORESCENT



## PROFILE LOUVER TYPE

### SPECIFICATION

#### HOUSING

- DIE-FORMED COLD-ROLLED STEEL  
AVAILABLE IN □ 0.4, □ 0.6, □ 0.8 mm.  
STEEL THICKNESS
- ALL METAL PART ARE RUST-PROOFED AFTER  
FABRICATION TO PREVENT ANY CORROSION  
(ZINE PHOSPHATE)
- FINISHED WITH HIGH GRADE EPOXY POLYESTER  
POWDER COATING
- G13 ROTARY LOCKED LAMP HOLDER
- THW □ 0.5 sqmm./105c □ 1.0 sqmm./70c  
WIRING CABLE

#### REFLECTOR & LOUVER

- 99.80% PURITY ANODIZED ALUMINIUM  
REFLECTOR TO PROVIDE TOTAL REFLECTANCE OF  
□ TR 87% □ TR 95% FOR MIRROR FINISH
- HIGH PRECISSION ROLLED FORMING MACHINE TO  
PROVIDE OPTIMUM OPTICAL PERFORMANCE FOR  
LONGITUDINAL
- CHRISTMAS TREE PROFILES FOR TRANSVERSAL

#### INSTALLATION

- AVAILABLE IN RECESSED T-BAR OR CONCEAL CEILING

### DIMENSIONS (mm.)

MODEL	TYPE	W	W1	L	L1	H	CEILING CUT OUT (mm.) A x B
WLR8/3/2S	T8	295	257	612	590	70	270 x 572
WLR8/6/2S	T8	595	557	612	590	70	570 x 572
WLR8/6/3S	T8	595	557	612	590	70	570 x 572
WLR8/3/2L	T8	295	257	1220	1197	70	270 x 1178
WLR8/6/2L	T8	595	557	1220	1197	70	570 x 1178
WLR8/6/3L	T8	595	557	1220	1197	70	570 x 1178

