



## PROFILE LOUVER TYPE

### SPECIFICATION

#### HOUSING

- DIE-FORMED COLD-ROLLED STEEL  
AVAILABLE IN  0.4,  0.6,  0.8 mm.  
STEEL THICKNESS
- ALL METAL PART ARE RUST-PROOFED AFTER  
FABRICATION TO PREVENT ANY CORROSION  
(ZINE PHOSPHATE)
- FINISHED WITH HIGH GRADE EPOXY POLYESTER  
POWDER COATING
- G13 ROTARY LOCKED LAMP HOLDER
- THW  0.5 sqmm./105c  1.0 sqmm./70c  
WIRING CABLE

#### REFLECTOR & LOUVER

- 99.80% PURITY ANODIZED ALUMINIUM  
REFLECTOR TO PROVIDE TOTAL REFLECTANCE OF  
 TR 87%  TR 95% FOR MIRROR FINISH
- HIGH PRECISSION ROLLED FORMING MACHINE TO  
PROVIDE OPTIMUM OPTICAL PERFORMANCE FOR  
LONGITUDINAL
- CHRISTMAS TREE PROFILES FOR TRANSVERSAL

#### INSTALLATION

- AVAILABLE IN RECESSED T-BAR OR CONCEAL CEILING

#### DIMENSIONS (mm.)

MODEL	TYPE	W	W1	L	L1	H	CEILING CUT OUT (mm.) A x B
WLR9/3/1S	T8	295	271	589	612	80	278 x 575
WLR9/3/2S	T8	295	257	589	612	80	270 x 575
WLR9/6/2S	T8	595	557	589	612	80	570 x 575
WLR9/6/3S	T8	595	557	589	612	80	570 x 575
WLR9/6/4S	T8	595	557	589	612	80	570 x 575
WLR9/3/1L	T8	295	271	1197	1220	80	278 x 1178
WLR9/3/2L	T8	295	257	1197	1220	80	270 x 1178
WLR9/6/2L	T8	595	557	1197	1220	80	570 x 1178
WLR9/6/3L	T8	595	557	1197	1220	80	570 x 1178
WLR9/6/4L	T8	595	557	1197	1220	80	570 x 1178

