



PROFILE LOUVER TYPE

SPECIFICATION

HOUSING

- DIE-FORMED COLD-ROLLED STEEL
AVAILABLE IN 0.4 , 0.6 , 0.8 mm.
STEEL THICKNESS
- ALL METAL PART ARE RUST-PROOFED AFTER FABRICATION TO PREVENT ANY CORROSION (ZINE PHOSPHATE)
- FINISHED WITH HIGH GRADE EPOXY POLYESTER POWDER COATING
- (G5, G13) ROTARY LOCKED LAMP HOLDER
- THW 0.5 sqmm./105c 1.0 sqmm./70c
WIRING CABLE

REFLECTOR & LOUVER

- 99.80% PURITY ANODIZED ALUMINIUM REFLECTOR TO PROVIDE TOTAL REFLECTANCE OF TR 87% TR 95% FOR MIRROR FINISH
- PARABOLIC REFLECTOR MACHINED TO PROVIDE OPTIMUM OPTICAL PERFORMANCE FOR LONGITUDINAL
- CHRISTMAS TREE PROFILES FOR TRANSVERSAL

INSTALLATION

- SURFACE OR SUSPENDED MOUNTING

DIMENSIONS (mm.)

MODEL	TYPE	W	L	H
WLS1/6/2S	T5 , T8	601	616	80
WLS1/6/3S	T5 , T8	601	616	80
WLS1/6/4S	T5 , T8	601	616	80
WLS1/6/2L	T5 , T8	601	1226	80
WLS1/6/3L	T5 , T8	601	1226	80
WLS1/6/4L	T5 , T8	601	1226	80

