



## PROFILE LOUVER TYPE

### SPECIFICATION

#### HOUSING

- DIE-FORMED COLD-ROLLED STEEL  
AVAILABLE IN  0.4,  0.6,  0.8 mm.  
STEEL THICKNESS
- ALL METAL PART ARE RUST-PROOFED AFTER  
FABRICATION TO PREVENT ANY CORROSION  
(ZINE PHOSPHATE)
- FINISHED WITH HIGH GRADE EPOXY POLYESTER  
POWDER COATING
- (G5, G13) ROTARY LOCKED LAMP HOLDER
- THW  0.5 sqmm./105c  1.0 sqmm./70c  
WIRING CABLE

#### REFLECTOR & LOUVER

- 99.80% PURITY ANODIZED ALUMINIUM  
REFLECTOR TO PROVIDE TOTAL REFLECTANCE OF  
 TR 87%  TR 95% FOR MIRROR FINISH
- PARABOLIC REFLECTOR MACHINED TO PROVIDE  
OPTIMUM OPTICAL PERFORMANCE FOR  
LONGITUDINAL
- CHRISTMAS TREE PROFILES FOR TRANSVERSAL

#### INSTALLATION

- SURFACE OR SUSPENDED MOUNTING

#### DIMENSIONS (mm.)

MODEL	TYPE	W	L	H
WLS2C/1S	T5	200	572	80
WLS2C/2S	T5	200	572	80
WLS2C/1L	T5	200	1172	80
WLS2C/2L	T5	200	1172	80
WLS2C/1S	T8	200	612	80
WLS2C/2S	T8	200	612	80
WLS2C/1L	T8	200	1220	80
WLS2C/2L	T8	200	1220	80

