



DOUBLE PARABOLIC LOUVER TYPE

SPECIFICATION

HOUSING

- DIE-FORMED COLD-ROLLED STEEL
AVAILABLE IN □ 0.4 , □ 0.6 , □ 0.8 mm.
STEEL THICKNESS
- ALL METAL PART ARE RUST-PROOFED AFTER
FABRICATION TO PREVENT ANY CORROSION
(ZINE PHOSPHATE)
- FINISHED WITH HIGH GRADE EPOXY POLYESTER
POWDER COATING
- G13 ROTARY LOCKED LAMP HOLDER
- THW □ 0.5 sqmm./105c □ 1.0 sqmm./70c
WIRING CABLE

REFLECTOR & LOUVER

- 99.80% PURITY ANODIZED ALUMINIUM
REFLECTOR TO PROVIDE TOTAL REFLECTANCE OF
□ TR 87% □ TR 95% FOR MIRROR FINISH
- HIGH SPECULAR REFLECTION AND LOW DIFFUSED
REFLECTION TO PROVIDE UNIFORM LIGHT
DISTRIBUTION AND LOW GLARE
- DEEP CALL PARABOLIC PROVIDE EXCELLENT
GLARE CONTROL

INSTALLATION

- SURFACE OR SUSPENDED MOUNTING

DIMENSIONS (mm.)

MODEL	TYPE	W	L	H
WLS5-S/3/1S	T8	300	616	90
WLS5-S/3/2S	T8	300	616	90
WLS5-S/6/2S	T8	600	616	90
WLS5-S/6/3S	T8	600	616	90
WLS5-S/3/1L	T8	300	1226	90
WLS5-S/3/2L	T8	300	1226	90
WLS5-S/6/2L	T8	600	1226	90
WLS5-S/6/3L	T8	600	1226	90

