



PROFILE LOUVER TYPE

SPECIFICATION

HOUSING

- DIE-FORMED COLD-ROLLED STEEL
AVAILABLE IN □ 0.4, □ 0.6, □ 0.8 mm.
STEEL THICKNESS
- ALL METAL PART ARE RUST-PROOFED AFTER
FABRICATION TO PREVENT ANY CORROSION
(ZINE PHOSPHATE)
- FINISHED WITH HIGH GRADE EPOXY POLYESTER
POWDER COATING
- (G5, G13) ROTARY LOCKED LAMP HOLDER
- THW □ 0.5 sqmm./105c □ 1.0 sqmm./70c
WIRING CABLE

REFLECTOR & LOUVER

- 99.80% PURITY ANODIZED ALUMINIUM
REFLECTOR TO PROVIDE TOTAL REFLECTANCE OF
□ TR 87% □ TR 95% FOR MIRROR FINISH
- PARABOLIC REFLECTOR MACHINED TO PROVIDE
OPTIMUM OPTICAL PERFORMANCE FOR
LONGITUDINAL
- CHRISTMAS TREE PROFILES FOR TRANSVERSAL

INSTALLATION

- SURFACE OR SUSPENDED MOUNTING

DIMENSIONS (mm.)

MODEL	TYPE	W	L	H
WLS8/3/2S	T5, T8	301	616	80
WLS8/6/2S	T5, T8	601	616	80
WLS8/6/3S	T5, T8	601	616	80
WLS8/3/2L	T5, T8	301	1226	80
WLS8/6/2L	T5, T8	601	1226	80
WLS8/6/3L	T5, T8	601	1226	80

