



## WEATHER-PROOF TYPE

### SPECIFICATION

#### HOUSING

- DIE-FORMED COLD-ROLLED STEEL AVAILABLE IN 0.8 mm. STEEL THICKNESS
- ALL METAL PART ARE RUST-PROOFED AFTER FABRICATION TO PREVENT ANY CORROSION (ZINE PHOSPHATE)
- FINISHED WITH HIGH GRADE EPOXY POLYESTER POWDER COATING
- (G5, G13) ROTARY LOCKED LAMP HOLDER
- THW  0.5 sqmm./105c  1.0 sqmm./70c WIRING CABLE

#### PROTECTION CLASS

- IP 65

#### OPTION REFLECTOR

- 99.80% PURITY ANODIZED ALUMINIUM REFLECTOR TO PROVIDE TOTAL REFLECTANCE OF  TR 87%  TR 95% FOR MIRROR FINISH

#### DIFFUSER

- FOR CLEAR ACRYLIC DIFFUSER

#### INSTALLATION

- SURFACE OR SUSPENDED MOUNT

#### REFLECTOR

- STEEL SHEET MATERIAL IN WHITE

### DIMENSIONS (mm.)

MODEL	TYPE	W	L	H
WPD7/1S	T5, T8	110	680	110
WPD7/2S	T5, T8	160	680	110
WPD7/1L	T5, T8	110	1286	110
WPD7/2L	T5, T8	160	1286	110

