


SPECIFICATION



Parameter	CitySpirit Street
Type	BDS480
Light Source	Mid Power LED
Power Consumption	37W 71W
Input Voltage	220-240V AC, 50/60 Hz
System lumen output	4200lm 8400lm
CRI	> 70
Connection	Complete with 6m flying cable
Control Interface	PSU: On/Off PSD: DALI-dimming CityTouch ready: Available upon request
Materials and finishing	Die-cast aluminum housing, tempered glass BDS480 Die-cast aluminum housing, tempered glass
Housing body colour	Ultra Dark Grey (RAL7022)
Lifetime	50K hours (70% lumen maintenance @ Ta = 35°C)
Mounting Pole Dimensions	Ø60mm
Weight	13.7Kg net weight
Classifications	Class I
IP / IK Grade	IP65; IK 09
Operating Temperature	- 40°C to + 50°C
Certifications	CB, CQC



TYPE	POWER	CCT	PRICE
BDS480 LED42/NW PSD 220-240V DW2 MP1 GM	37W	4000K	30,900
BDS480 LED42/NW PSU 220-240V DW2 MP1 GM	37W	4000K	28,200
BDS480 LED42/WW PSD 220-240V DW2 MP1 GM	37W	3000K	30,900
BDS480 LED42/WW PSU 220-240V DW2 MP1 GM	37W	3000K	28,200
BDS480 LED84/NW PSD 220-240V DW2 MP1 GM	71W	4000K	32,800
BDS480 LED84/NW PSU 220-240V DW2 MP1 GM	71W	4000K	29,900
BDS480 LED84/WW PSD 220-240V DW2 MP1 GM	71W	3000K	32,800
BDS480 LED84/WW PSU 220-240V DW2 MP1 GM	71W	3000K	29,900

* (ราคาไม่รวมเสาไฟและฐานราก)

